

TULIP XL

by Moredesign




Indoor use

Outdoor use



MYOUR®





cod. 6001 ITUL		SEE AVAILABLE COLOURS AT PAGE 158		
MATERIAL	COLORS	€ VAT EXCLUDED		
EMBOSSED MOULDED (GS)	WHITE	117	325	
	BLACK	210	325	
	ORANGE	388	325	
	LILAC	404	325	
	RED	204	325	
	IVORY	602	325	
	GREEN	662	325	
GLOSSY ENAMELLED (LV)	WHITE	117	1.121,50	
	BLACK	210	1.121,50	
	ORANGE	388	1.121,50	
	LILAC	404	1.121,50	
	RED	204	1.121,50	
	IVORY	602	1.121,50	
	GREEN	662	1.121,50	

SHIPMENT SPECIFICATIONS	TECHNICAL CHARACTERISTICS
Packages: 1 Gross weight: kg 11 Net weight: kg 7 Packaging: P 38 x L 38 x H 152 cm / 0,22 m ³	Poleasy © with excellent mechanical properties, UV stabilized for outdoor applications. It is possible to dock Tulip XL by filling it with sand or water.



MYOUR®

- Indoor use
- Outdoor use



SEE AVAILABLE COLOURS AT PAGE 158

cod. 6011ITUL

MATERIAL	COLORS	€ VAT EXCLUDED	
EMBOSSED MOULDED (GS) - WITH LIGHT (IL)	TRANSPARENT 110	575	
	GREEN 662	575	
	ORANGE 388	575	
	LILAC 404	575	
	RED 204	575	

SHIPMENT SPECIFICATIONS	TECHNICAL CHARACTERISTICS	TESTS
Packages: 1 Gross weight: kg 13,10 Net weight: kg 8,5 Packaging: P 38 x L 38 x H 152 cm / 0,22 m³	Poleasy® diffuser. Protection index: IP44 Type of lighting: Fluorescent tube. T528W L 110 cm (not supplied) (Philips T528WV cod. master TL5HE28WV/840) Length of power cable: 1,85 m (without switch)	CEI EN60598-1 8 ^{ed.} 05.2005 CEI EN60598-2-7 (CEI 34-28)



TULIP XL LIGHT


by Moredesign



Indoor use
Outdoor use



MYOUR®



cod. 6021 ITUL (IL) - (EU)		SEE AVAILABLE COLOURS AT PAGE 158	
MATERIAL	COLORS	€ VAT EXCLUDED	
EMBOSSED MOULDED (GS) - WITH LIGHT (IL)	TRANSPARENT 110	575	
	GREEN 662	575	
	ORANGE 388	575	
	LILAC 404	575	
	RED 204	575	


SHIPMENT SPECIFICATIONS	TECHNICAL CHARACTERISTICS	TESTS
Packages: 1 Gross weight: kg 13,10 Net weight: kg 7+1,5 (luce) Packaging: P 38 x L 38 x H 152 cm / 0,22 m ³	Poleasy® diffuser. Protection index: IP40 Type of lighting: Fluorescent tube. T528W L 110 cm (not supplied) (Philips T528W cod. master TL5HE28W/840) Length of power cable: 3,20 m 	EN60598-1 (CEI 34-21) 8°ed. 05.2005 EN60598-2-4 (CEI 34-29) 4°ed. 06.1998

TULIP XL



FIXING PLATE



Indoor use
Outdoor use



MYOUR®



cod. 90012TUL	
MATERIAL	€ VAT EXCLUDED
GALVANIZED STEEL	61,50

SHIPMENT SPECIFICATIONS	TECHNICAL CHARACTERISTICS
Packages: 1 Gross weight: kg 2 Net weight: kg 1 Packaging: P 27 x L 36 x H 4 cm / 0,004 m ³	Cold galvanized steel (anchor bolts not included). (available only for Tulip XL with light).

TULIP XL

LIGHTING KIT FOR OUTDOOR



	cod. 60111KIT (EU) cod. 60311KIT (USA) cod. 60411KIT (UK) cod. 60412KIT (AUS)
€ VAT EXCLUDED	
275	

SHIPMENT SPECIFICATIONS
Packages: 1 Gross weight: kg 2,10 Net weight: kg 1,5 Packaging: P 38 x L 38 x H 152 cm / 0,22 m ³

TULIP XL

LIGHTING KIT FOR INDOOR



	cod. 60211KIT - (EU)
€ VAT EXCLUDED	
275	

SHIPMENT SPECIFICATIONS
Packages: 1 Gross weight: kg 2,10 Net weight: kg 1,5 Packaging: P 38 x L 38 x H 152 cm / 0,22 m ³



TULIP S

by Moredesign



MYOUR®

- Indoor use
Outdoor use



SEE AVAILABLE COLOURS AT PAGE 158

MATERIAL	COLORS	€ VAT EXCLUDED	cod. 60010TUL
EMBOSSSED MOULDED (GS)	WHITE 117	90	
	BLACK 210	90	
	ORANGE 388	90	
	LILAC 404	90	
	RED 204	90	
	IVORY 602	90	
	GREEN 662	90	

SHIPMENT SPECIFICATIONS	TECHNICAL CHARACTERISTICS
Packages: 1 (2 pcs/box) (minimum of purchase: 2 pieces of the same color). Gross weight: g 900 Net weight: g 300 Packaging: P 46,4 x L 46,4 x H 15 cm / 0,01 m ³	Poleasy® with excellent mechanical properties, UV stabilized for outdoor applications.

TULIP S LIGHT


by Moredesign



- Indoor use
- Outdoor use



MYYOUR®



cod. 60210TUL*		SEE AVAILABLE COLOURS AT PAGE 158	
MATERIAL	COLORS	€ VAT EXCLUDED	
EMBOSSED MOULDED (GS) - WITH LIGHT (IL)	TRANSPARENT 110	195	
	GREEN 662	195	
	ORANGE 388	195	
	LILAC 404	195	
	RED 204	195	

* it's available only with european lighting.

SHIPMENT SPECIFICATIONS	TECHNICAL CHARACTERISTICS	TESTS
Packages: 1 (2 pcs/box) (minimo acquisto 2pz dello stesso colore). Gross weight: Kg 1,3 Net weight: g 500 Packaging: P 46,4 x L 15,4 x H 15 cm / 0,01 m ³	Poleasy® diffuser. Protection index: IP40 7 integrated leds, tot 3W Power feed: 230V 50/60 HZ 2° class, F marking 3° class low voltage F3123 CEE, 93-68-CE Length of power cable: 1,70 m 	EN60598-1 (CEI 34-21) 8°ed. 05.2005 EN60598-2-4 (CEI 34-29) 4°ed. 06.1998